

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8228 (1976): Bauxite Sand [MTD 14: Foundry]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 8228 - 1976

Indian Standard
SPECIFICATION FOR BAUXITE SAND

UDC 621.742.42 : 622.349.21



© Copyright 1977

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Price Rs **5.00**

January 1977

Indian Standard

SPECIFICATION FOR BAUXITE SAND

Foundry Sectional Committee, SMDC 17

Chairman

SHRI N. G. CHAKRABARTI
3/D, Nandi Street, Calcutta 700029

Members

SHRI M. C. AICH
SHRI M. ANJANEYULU

SHRI S. R. SENGUPTA (*Alternate*)

SHRI P. D. BAJORIA

SHRI H. N. SEN (*Alternate*)

SHRI R. M. BALANI

SHRI V. D. SHARMA (*Alternate*)

SHRI B. N. BALIGA

SHRI S. D. BHAGWAT (*Alternate*)

SHRI D. N. BANERJEE

SHRI K. NAGESHA RAO (*Alternate*)

SHRI R. K. BHOWMICK

SHRI A. K. CHATTERJEE

SHRI D. P. JAIN (*Alternate*)

DEPUTY DIRECTOR (MET-I), Ministry of Railways

RESEARCH, DESIGNS AND
STANDARDS ORGANIZATION,
LUCKNOW

CHEMIST & METALLURGIST

(SF), CHITTARANJAN

LOCOMOTIVE WORKS,

CHITTARANJAN (*Alternate I*)

DEPUTY CHIEF MECHANICAL

ENGINEER (MFG),

CHITTARANJAN LOCO-

MOTIVE WORKS, CHITTA-

RANJAN (*Alternate II*)

Representing

Directorate General of Supplies & Disposals
(Inspection Wing)

Mining & Allied Machinery Corporation Limited,
Durgapur

J. D. Jones & Co Limited, Calcutta

Directorate General of Technical Development,
New Delhi

Cooper Engineering Limited, Satara Road,
Maharashtra

Hindustan Machine Tools Ltd, Bangalore

Bhartia Electric Steel Co Ltd, Calcutta

Indian Non-ferrous Metals Manufacturers'
Association, Calcutta

(Continued on page 2)

© Copyright 1977

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

SHRI M. S. DESHPANDE
SHRI M. S. DUA
DR A. M. GUPTA

SHRI P. L. JAIN (Alternate)

SHRI G. C. GUPTA

SHRI K. V. GURRAM

SHRI B. K. SARKAR (Alternate)

SHRI B. N. HANDA

SHRI S. C. JAIN

SHRI F. S. KATPITIA

SHRI M. R. SHAH (Alternate)

SHRI Y. N. KAUSHAL

SHRI J. S. KHATTAU

SHRI S. BHARDWAJ (Alternate)

SHRI R. C. KOTHARI

SHRI D. G. KULKARNI

SHRI V. T. BALASUBRAMANIAN (Alternate)

SHRI K. N. MEHRA

SHRI A. K. BANERJEE (Alternate)

LT CDR K. B. MEHTA

SHRI P. C. MULLICK

SHRI S. N. AGRAWAL (Alternate)

SHRI P. C. NEOGY

SHRI J. V. GADGIL (Alternate)

SHRI N. V. PANDIT

SHRI H. S. PAUL

SHRI M. K. PRAMANIK

SHRI G. N. RAO

SHRI S. N. RAO

SHRI J. N. BERA (Alternate)

REPRESENTATIVE

SHRI D. SANYAL

SHRI B. L. SEN

SHRI R. K. SRIVASTAVA

SHRI Z. M. BHATE (Alternate)

SHRI V. N. SUNDERRAJAN

SHRI S. THIYAGARAJAN

SHRI J. N. VARMA

DR V. P. GUPTA (Alternate)

DR P. VASUDEVAN

SHRI C. R. RAMA RAO,

Director (Struc & Met)

Representing

New Precision (India) Pvt Limited, Dewas
In personal capacity (167, Sector 11-A, Chandigarh)
National Institute of Foundry & Forge Technology,
Ranchi

Arch Industries Corporation, Calcutta
Delhi Cloth & General Mills Co Limited, New Delhi

Uttar Pradesh Steels Ltd, Muzaffarnagar
Jay Engineering Works Ltd, Calcutta
Jyoti Limited, Vadodara

Indian Foundry Association, Calcutta
Godrej & Boyce Mfg Co Pvt Limited, Bombay

Pioneer Equipment Co Pvt Ltd, Vadodara
Institute of Indian Foundrymen, Calcutta

Heavy Engineering Corporation Ltd, Ranchi

Ministry of Defence (NHQ)
Electrosteel Castings Limited, Calcutta

Indian Iron & Steel Co Ltd, Burnpur

M. M. Suri & Associates (P) Limited, New Delhi
Machinery Manufacturers Corp Limited, Calcutta
Iron & Steel Control, Calcutta
National Metallurgical Laboratory (CSIR),
Jamshedpur
Laxmi Starch Limited, Calcutta

Hindustan Steel Limited (R & D), Ranchi
Coal Controller (Ministry of Energy), Calcutta
Indian Oxygen Limited, Calcutta
Mukand Iron & Steel Works Limited, Bombay

M. N. Dastur & Co Pvt Ltd, Calcutta
Southern Alloy Foundries Private Ltd, Madras
Tata Engineering & Locomotive Co Ltd,
Jamshedpur

Indian Institute of Metals, Calcutta
Director General, ISI (Ex-officio Member)

Secretary

SHRI SHANTI SWARUP
Assistant Director (Metals), ISI

(Continued on page 7)

Indian Standard

SPECIFICATION FOR BAUXITE SAND

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 29 September 1976, after the draft finalized by the Foundry Sectional Committee had been approved by the Structural and Metals Division Council.

0.2 Bauxite sand is prepared by first calcining bauxite to above 1 400°C to reduce shrinkage and then crushing the calcined bauxite.

0.2.1 Bauxite sand requires very little bond addition as the fines of bauxite act as a bond. Bauxite being amphoteric in nature, it is not reactive towards manganese steel. Bauxite sand is, therefore, normally preferred for the high manganese steel castings.

0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers the requirements for bauxite sand for use in foundries.

2. SUPPLY OF MATERIAL

2.1 General requirements relating to the supply of bauxite sand shall be as laid down in IS : 1387-1967†.

3. MOISTURE CONTENT

3.1 Moisture content of bauxite sand when tested in accordance with the method given in IS : 1918-1966‡ shall not exceed 1.0 percent.

*Rules for rounding off numerical value (*revised*).

†General requirements for the supply of metallurgical materials (*first revision*).

‡Methods of physical tests for foundry sands.

4. CHEMICAL COMPOSITION

4.1 Bauxite sand shall have the following composition on dry weight basis, when tested in accordance with the procedure specified in IS: 2000-1962*:

<i>Constituent</i>	<i>Requirement, Percent</i>
Al_2O_3	75 <i>Min</i>
Fe_2O_3	5 <i>Max</i>
$\text{CaO} + \text{MgO}$	1 <i>Max</i>
TiO_2	10 <i>Max</i>
SiO_2	10 <i>Max</i>
Alkalies	0.5 <i>Max</i>
Loss on ignition	0.5 <i>Max</i>

5. FUSION POINT

5.1 When tested in accordance with IS: 1528 (Part I)-1974† the PCE value of bauxite sand shall be not below standard pyrometric cone (ASTM) No. 35 (1 800°C).

6. GRAIN SHAPE

6.1 When tested in accordance with IS: 1918-1966‡, the grains shall be angular to subangular.

7. GRAIN FINENESS

7.1 The fineness of the bauxite sand shall conform to the following requirements:

<i>IS Sieve</i>	<i>Percent Retained</i>
4.00 mm	Nil
3.35 mm	5 <i>Max</i>
1.70 mm	10 <i>Max</i>
850-micron	20-25
600-micron	15-20
425-micron	10-15
300-micron	10-15
212-micron	5-10
150-micron	5-10
106-micron	5 <i>Max</i>
Pan	10-15
Grain fineness No.	35-40

*Methods of chemical analysis of bauxite.

†Methods of sampling and physical tests for refractory materials: Part I Determination of pyrometric cone equivalent (PCE) or softening point (first revision).

‡Methods of physical tests for foundry sands.

7.2 If required, bauxite sand with fineness other than that specified in 7.1 may be supplied subject to the agreement between the purchaser and the manufacturer.

NOTE — When IS sieves (*see* IS : 460-1962*) are not available, equivalent BS or ASTM test sieves specified in Appendix A may be used. The BS and ASTM sieves listed in Appendix A have the apertures within the limits specified for the corresponding IS sieves.

8. CLAY CONTENT

8.1 The clay content, when determined in accordance with IS : 1918-1966†, shall not exceed 1 percent.

9. PACKING

9.1 Unless specified otherwise, bauxite sand shall be supplied in polythene-lined gunny bags each containing 50 kg.

10. MARKING

10.1 The bags containing bauxite sand shall be clearly marked with the supplier's name or trade-mark.

10.1.1 The material may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

*Specification for test sieves (*revised*).

†Methods of physical tests for foundry sands.

A P P E N D I X A*(Clause 7.2)***COMPARATIVE SIEVE DESIGNATIONS OF
IS, BS AND ASTM TEST SIEVES**

<i>IS Sieve</i>	<i>BS Test Sieve</i>	<i>ASTM Test Sieve</i>
4·00 mm	—	5
3·35 mm	5	6
1·70 mm	10	12
850-micron	18	20
600-micron	25	30
425-micron	36	40
300-micron	52	50
212-micron	72	70
150-micron	100	100
106-micron	150	140

(Continued from page 2)

Foundry Silica Sand Subcommittee, SMDC 17 : 1

Convener

DR V. P. GUPTA

*Representing*Tata Engineering & Locomotive Co Limited,
Jamshedpur*Members*SHRI A. B. BHATTACHARJEE (*Alternate to*
Dr V. P. Gupta)

SHRI ANAND AGRAWAL

Silica Khaniz Udyog, Allahabad

SHRI R. M. BALANI

Directorate General of Technical Development,
New DelhiSHRI V. D. SHARMA (*Alternate*)

SHRI D. K. DAS

Heavy Engineering Corp Ltd, Ranchi

DEPUTY DIRECTOR (MET)-3,

Ministry of Railways

RESEARCH, DESIGNS & STANDARDS ORGANIZATION,
LUCKNOWCHEMIST & METALLURGIST
(STEEL FOUNDRY),

CHITTARANJAN LOCOMOTIVE WORKS, CHITTA-

RANJAN (*Alternate*)

SHRI JITENDRA MOHAN

Mukand Iron & Steel Works Limited, Bombay

SHRI Z. M. BHATE (*Alternate*)

SHRI B. S. MANJREKAR

Geological Survey of India, Calcutta

SHRI G. N. RAO

National Metallurgical Laboratory (CSIR),
JamshedpurSHRI T. A. BECK (*Alternate*)

REPRESENTATIVE

Dalmia Agencies, Rajmahal

SHRI P. K. SANDELL

Bhartia Electric Steel Company Limited, Faridabad

SHRI G. SRIVASTAVA (*Alternate*)

INDIAN STANDARDS

ON

FOUNDRY

IS:

- 1280-1975 Foundry moulding boxes of steel construction (*second revision*)
- 1305-1967 Graphite for use as foundry facing material (*second revision*)
- 1513-1971 Pattern equipment for foundries (*first revision*)
- 1752-1973 Coal dust for use in cast iron foundry (*second revision*)
- 1811-1961 Methods of sampling foundry sands
- 1918-1966 Methods of physical tests for foundry sands
- 1987-1974 High silica sand for use in foundries (*first revision*)
- 3339-1975 Silica flour for use in foundries (*second revision*)
- 3343-1975 Natural moulding sand for use in foundries (*first revision*)
- 3666-1966 Tests for foundry core oils requiring baking
- 4140-1967 Limestone for use in foundries
- 4269-1967 Dextrin for use in foundries
- 4475-1975 Crane-suspended hand-operated geared ladles for iron foundries (*first revision*)
- 4476-1975 Crane-suspended hand-operated geared ladles for steel foundries (*first revision*)
- 4604-1975 Pattern plates for machine moulding boxes (*first revision*)
- 4606-1968 Steel shot for use in foundries
- 4683-1968 Chilled iron shot and grit for use in foundries
- 4981-1975 Guide pins for foundry pattern plates (*first revision*)
- 4982-1975 Closing pins for foundry moulding boxes (*first revision*)
- 5032-1975 Recommended sizes of cupola furnace for foundry (*first revision*)
- 5303-1974 Zircon flour for use in foundries (*first revision*)
- 5824-1970 Lancets for use in foundries
- 5841-1970 Fluted core cleaners for use in foundries
- 5850-1970 Star (triangular) cutters for use in foundries
- 5873-1970 Steel cut-wire shots for use in foundries
- 5904-1970 Chaplets for use in foundries
- 5981-1970 Slickers for use in foundries
- 5988-1970 Spring dowel sleeves (light and heavy patterns) for use in foundries
- 6013-1970 Trowels for use in foundries
- 6366-1971 Sprue plugs for use in foundries
- 6376-1971 Pattern lifting pins and hooks for use in foundries
- 6377-1971 Mallets for use in foundries
- 6378-1971 Pattern lifting and rapping plates
- 6401-1971 Dowel pins for use in foundries
- 6443-1971 Lifters and cleaners for use in foundries
- 6447-1971 Vent wires for use in foundries
- 6482-1971 Tampers and rammers for use in foundries
- 6773-1973 Sodium silicate for use in foundries
- 6788-1973 Chromite sand for use in foundries
- 7295-1974 Chamotte
- 7297-1974 Olivine sand and flour for use in steel foundries
- 7547-1974 Steel nails used as internal chills in steel castings

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

Over 8 500 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Structural and Metals Group fall under the following categories:

Brazing alloys and solders	Power metallurgical materials and products
Copper and copper alloys	Precious metals
Corrosion protection	Quality control
Cranes and allied appliances	Refractories
Design codes	Steel castings
Ferro-alloys	Steel forgings
Foundry raw materials and equipment	Steel products, wrought and alloy
Lead, zinc, tin, antimony and their alloys	Steel tubes, pipes and fittings
Light metals and their alloys	Structural shapes
Metallic finishes	Welding
Metallography and heat treatment	Unclassified
Non-destructive testing	Engineers' slide
Ores and raw materials	Handbook for welders
Pig Iron, cast iron and malleable cast iron	ISI handbooks for structural engineers
	Steam tables

OTHER PUBLICATIONS

ISI Bulletin (Published Every Month)

Single Copy	Rs 4-00
Annual Subscription	Rs 36-00
Standards: Monthly Additions					
Single Copy	Rs 0-30
Annual Subscription	Rs 3-00
Annual Reports (from 1948-49 Onwards)	Rs 2-00 to 6-00	
ISI Handbook, 1975	Rs 30-00

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephone : 27 01 31 (20 lines)

Telegrams : Manaksanstha

Regional Offices :

	Telephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007 37 97 29
Eastern : 5 Chowringhee Approach	CALCUTTA 700072 23-08 02
Southern : C.I.T. Campus, Adyar	MADRAS 600020 41 24 42

Branch Offices :

'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001 2 03 91
'F' Block, Unity Bldg, Narasimharaja Square	BANGALORE 560002 2 76 49
Ahimsa Bldg, SCO 82-83, Sector 17C	CHANDIGARH 160017 2 83 20
5-8-56/57 L. N. Gupta Marg	HYDERABAD 500001 4 57 11
117/418 B Sarvodaya Nagar	KANPUR 208005 82 72
B.C.I. Bldg (3rd Floor), Gandhi Maidan East	PATNA 800004 5 36 55
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001 32 27